



### Product features and key data

<b>Luminaire type</b>	Round LED downlight
<b>Mounting method</b>	Recessed, with edge
<b>Application</b>	Sales rooms   Foyers   Corridors   Conference rooms   Hotels and restaurants   Residential areas
<b>UGR</b>	< 19
<b>Luminaire optic</b>	Specular reflector, 60° luminaire distribution beam angle
<b>Power supply value</b>	21 W
<b>Colour temperature</b>	3000/4000/5700K (Multi - color option)
<b>Rated light current</b>	1400/1600/ 1800/ 2000 lm (Multi-lumen option)
<b>Power Tolerance</b>	+/- 10%
<b>Luminous efficiency</b>	90 lm/W
<b>Colour rendering indx</b>	> 80
<b>Service life (L70B50)</b>	50.000 hrs
<b>Luminaire Body</b>	Die-cast aluminum
<b>Colour</b>	White trim with specular reflector
<b>Switching type</b>	Electronic Switchable
<b>Connection Method</b>	Direct
<b>Ambient temperature</b>	0° C to + 35° C
<b>Rated frequency</b>	50/60 Hz
<b>DC suitability</b>	Yes
<b>Protection rating on room side</b>	IP54
<b>Protection class</b>	II
<b>Impact resistance</b>	IK06
<b>Net height</b>	90 mm
<b>Outer diameter</b>	172 mm
<b>Cutout Ø</b>	150 - 165 mm
<b>Weight</b>	2,0 kg

### Light distribution curve

