


Product information Naviona M73 155



Product description


Recessed TC-L 55w fluorescent luminaire with secondary reflection system, back lit satin diffuser panels and central fine prism optic.

Application

Recommended for offices, conference rooms, sales areas, financial institutions and other circulation areas, for ceilings with 600mm exposed grid modules.

Optical system

Double-reflection system made of sheet steel, satin back lit side panels for wide-angle distribution and centrally mounted high performance fine prism optic.



Luminaire body

Sheet steel, white. Gear tray made of galvanised sheet steel.

Control gear option

With standard electronic control gear (E)
With Dali dimmable electronic control gear (EDD)

Emergency versions

3-hour integral emergency versions available.

Ordering information

TK10101264 - Naviona M73 155 E 01 - Standard H/F control gear
TK10101265 - Naviona M73 155 E 01 EM3 - Standard H/F control gear c/w 3 hour integral emergency
TK10101266 - Naviona M73 155 EDD 01 - Dali dimmable H/F control gear
TK10101267 - Naviona M73 155 EDD 01 EM3 - Dali dimmable H/F control gear c/w 3 hour integral emergency

Degree of protection	IP 20
Safety class	I
hot wire test	650 ° C
shock resistance	0,2 J
LFEC	F8
Cibse	BZ 5/1.5/BZ 4
LOR	79